

The Operation Codes Free Format Left Behind

Operation Code	Free Format Alternative
ADD	The plus operator (+)
ADDDUR	The plus operator (+) and date BIFS
ALLOC	%ALLOC
ANDxx	AND
BITOFF	%BITAND, %BITNOT
BITON	%BITOR
CABxx	Logical expressions
CALL	CALLP
CALLB	CALLP
CASxx	SELECT/WHEN/OTHER Block
CAT	The plus operator (+)
CHECK	%CHECK
CHECKR	%CHECKR
COMP	Logical expressions
DEFINE	D-specs with LIKE
DIV	The slash operator (/) or %DIV
DO	FOR
DOUxx	DOU
DOWxx	DOW
EXTRCT	%SUBDT
GOTO	Iter, Leave, and LeaveSR
Ifxx	IF
KFLD	The %KDS data structure
KLIST	The %KDS data structure
LOOKUP	%LOOKUPxx or %TLOOKUPxx
MHHZO	%BITAND, %BITOR
MHLZO	%BITAND, %BITOR
MLHZO	%BITAND, %BITOR
MLLZO	%BITAND, %BITOR
MOVE	EVALR, %SUBST, conversion functions
MOVEA	%SUBST, %SUBARR, conversion functions
MOVEL	%SUBST, conversion functions
MULT	The asterisk operator (*)
MVR	%REM
OCCUR	The array data structure
Orxx	OR
PARM	PR/PI definitions
PLIST	PR/PI definitions
REALLOC	%REALLOC
SCAN	%SCAN
SETOFF	Assignment expressions
SETON	Assignment expressions
SHTDN	%SHTDN
SQRT	%SQRT
SUB	The minus operator (–)
SUBDUR	The minus operator (–), %DIFF, date functions
SUBST	%SUBST
TAG	Iter, Leave and LeaveSR
TESTB	%BITAND
TESTN	MONITOR, ON-ERROR
TESTZ	%BITAND
TIME	%DATE, %TIME, %TIMESTAMP
WHENxx	WHEN
XFOOT	%XFOOT
XLATE	%XLATE
Z-ADD	EVAL and the plus operator (+)
Z-SUB	EVAL and the minus operator (–)